

# AxTALK-RM

## Rechargeable Rackmount Communicator with internal charger



The AxTALK-RM is a Rechargeable Rackmount Communication System designed for Commercial Diving Operations. This communicator has an internal rechargeable 12 VDC battery and an internal battery charger. The system has individual volume control for each channel so the supervisor can adjust manually the gain on each channel available among the two divers, the tender, the auxiliary input for music and the external audio output for recording. When used with an AxVIEW Video Recording System, the communications can be recorded with the video on a computer or on a PVR.

### Advanced Technology

- Rackmount enclosure & RUGGED components
- Internal Power Supply with Battery Charger
- Robust technologies in one small enclosure
- Individual Volume Control for earphone and microphone for each channel
- Divers can be set individually to 2-wire or 4-wire mode
- Audio Input (AUX) for smartphone music to divers with Volume Adjustment
- Audio Output to recorder with Volume Adjustment (+/-)
- Optional Blackbox Audio Recorder on a 64GB TF Card

### Ordering Information (Product Code – Description)

<b>AxTALK 2-RM</b>	Rechargeable Rackmount Communicator with Internal Charger (2-diver)
<b>COMREC-64GB</b>	Blackbox Audio Recorder for Communication Systems, 64GB
<b>HAND_MIC</b>	Hand Microphone with bananas for AxTALK
<b>RM-OPT-COM-EXT</b>	Communication Extender for two (2) Rackmount and one (1) Portable Systems installation
<b>AxTALK_BT_ADAPTER</b>	Bluetooth Wireless Adapter for AxTALK with External Switch
<b>HEADSET_BT_HEAD</b>	Bluetooth Wireless Headset for AxTALK for long Range Communication (available in HAT version)
<b>Remote_SPKR_KIT</b>	Remote Speaker with amplifier and wall volume Control.

### Specifications

#### General

Audio Input/Output :	1 per Diver (2)
(Bananas)	1 for the Supervisor/Tender
Microphone :	1 Integrated Microphone
Audio Output (BNC) :	1 (for recording)
Audio Volume Control :	1 per Diver (2)
	1 for the Tender
	1 for the AUX input
	1 for the AUDIO output
Operating Temp. (°F) :	-4 to 122 (-20 to 50°C)

#### Electrical

Power Inlet 1 :	90-240 VAC 50/60 Hz (IEC320C14)
Power Cable :	N. America (NEMA 5-15P)
	Europe (CEE 7/7)
	UK (BS1363A)
	Australia (AS 3112)
	India/South Africa (BS546A)

#### Mechanical

Dimensions (in) :	19 x 11 x 5 (Rackmount 4U)
	(48cm x 28cm x 13cm)
Weight (lbs) :	15.9 (7.0 kg)



[www.axsub.com](http://www.axsub.com)

112, Montee Industrielle-et-Commerciale, Suite 200  
Rimouski (Québec) CANADA G5M 1B1  
Phone : +1.418.731.1539 sales@axsub.com

Revision 1  
2022-JAN-19

